


Illuminated Push Button Switch Component EFIB Series

❖ Technical Data

- Protection Class
 - Illuminated Switch module IP66 in conjunction with Ex-enclosure & actuator
- Certification
 - Ex de IIC
 - IECEx KTL 11.0002U
 - INERIS 13 ATEX 9004U
- Rating
 - Switch : Max. AC 250V / Max. DC 110V / 16A
 - Lamp : Max. AC 250V / Max. DC 110V / 20mA
 - Power $\leq$ 1W
- Material
 - Body : PC (Polycarbonate)
 - Contact : Silver-nickel (Standard)
- Connection
 - Max. 4mm²
- Light Source
 - LED
- luminance
 - 1200 cd/m²
- Lamp color
 - Red, Yellow, Green, Blue, White
- Weight
 - 110g
- Assembly with actuator IB

❖ Dimension



❖ Selection Chart

Type of Contact	Diagram	Order Code
1NC / 1NO		EFIB 01
2NC		EFIB 02
2NO		EFIB 03

Ampere Meter Component EFAM Series

❖ Technical Data

- Protection Class
 - Ampere Meter IP66 in conjunction with Ex-enclosure & actuator
- Certification
 - Ex eb IIC Gb
 - IECEx KTL 17.0023U
 - INERIS 19 ATEX 9004U
- Rating
 - Max. 5A
- Material
 - Body : PA6 (Polyamide6)
 - Lens : PC (Polycarbonate)
- Connection : Max. 4mm²
- This Ampere meter is for AC Voltage only.

❖ Dimension

